



THE CHINKLESS ALTERNATIVE™

ADVANCED TEXTURED CAULK DESIGNED TO SUBTLY BLEND WITH LOG FINISHES

Product Description

Timber Match™ is a new, state-of-the-art textured product designed to blend in with today's most popular stain colors. Timber Match can be either a chinking alternative for those who prefer to minimize a noticeable chink line but require a weather and pest tight seal or for filling checks, cracks and corners in the most subtle way possible.

Product Features

The Chink-less Alternative™

- ✓ color pallet provides a “mirage” effect
- ✓ closely matches hues of stained wood
- ✓ remains flexible and pliable after full cure even at low temperatures.
- ✓ high solids content, reduced shrinkage
- ✓ fill and conceal weather checks and voids
- ✓ exterior and interior sealant
- ✓ easy to apply and tool
- ✓ advanced mildew and fungal inhibitors
- ✓ paint-able and stainable
- ✓ soap and water clean-up

Performance Standards

Timber Match is formulated to surpass the industry performance standards for adhesion, elongation and tensile strength.

- ✓ ASTM C834 – Latex Sealants
- ✓ ASTM D-638 – Tensile Properties (elongation: 300%, tensile strength: 42 lbs/in²)
- ✓ ASTM-C920(12.5) – Elastomeric Joint Sealant

Precautions

Do not take internally.
Keep out of the reach of children.

General Production Information

Colors: Pinewood, Woodlands, Weathered Gray, Pine Cone, Café, Light Pine, Teak, Pine, Spruce, Natural, Redwood, Cedar

Packaging: 5-gallon pails, 29 fluid oz. fiber cartridges (10 per carton) and 10.5 fluid oz. plastic tubes (12 per carton)

Shelf Life: 12 months from purchase when stored in a tightly sealed container between 45°F and 90°F.

VOC: 35 grams/liter

Cure Time: 3 weeks (1/2” thickness, 77°F, 50% relative humidity). Timber Match is tack-free in 1-2 hours.

Freeze-Thaw: Passes 5 cycles

Slump: <1/16” (ASTM D2202)

Service Range: -30°F to 220°F

Application Range: 40°F to 95°F

Weathering: No washout, no cracking and no discoloration. UV resistance QUV (1000 hours) testing shows no effect.

Compatibility: Compatible with most sealers, preservatives and stains. Some coatings contain wax or petroleum based oils that can make adhesion more difficult.

Hazard Warning

Health	1
Flammability	0
Reactivity	0

